

PM 55

The compact precision DMM with AutoTest™ and VolTest™



- AutoTest™ feature directs the meter to know if it is measuring ac volts, dc volts or resistance with no user interface
- The AutoTest™ feature has lower input impedance which zeros out ghost voltages
- Measures ac/dc current, capacitance, frequency, continuity with beeper plus includes VolTest™ a built-in, non-contact voltage detector
- Complete user protection with full safety ratings of CAT III 300 V, CAT II 600 V and UL and CSA listing
- Large oversize digital display
- Protective silicon holster included, attached test leads, battery, deluxe carry case and manual
- One-year, no-hassle warranty

The ultimate shirt-pocket sized meter. Only 3/8" thick and less than 3 oz in weight with full functionality offering ac and dc voltage to 600 V, ac and dc current to 2000 μ A, resistance to 6 Megohm, capacitance to 2000 μ F, frequency to 30 kHz, diode test and continuity w/beeper. It also offers VolTest™ a built-in, non-contact voltage detector for ac voltages.

Another key feature is AutoTest™, which automatically selects between ac voltage, dc voltage or resistance measurement based on the test point to which the leads are

connected. Fully autoranging, this meter offers nine different measurement functions plus features that are usually found in much more expensive and larger meters.

The digital display is oversized with large digits and unit icons in the display. In spite of its size, this meter is fully safety rated to CAT III 300 V, CAT II 600 V and is UL listed. No other meter this small offers such performance and high safety ratings. Includes a silicone protective holster, deluxe carrying case, attached test leads, battery and manual.

PM 55 Specifications (Accuracy at 23 °C \pm 5 °C, <75 % R.H.)

RF field @ 3 V/m	Specified accuracy + 45 d (capacitance not specified)
DC Voltage	
Range	Accuracy
6.000 V	\pm (0.5 % + 3 dgt)
60.00 V	\pm (1.0 % + 5 dgt)
600 V	2.0 % (AutoTest™ Lo-Z)
600 V	1.5 % + 5 dgt (Hi-Z only)
NMRR	> 30 dB @ 50 Hz/60 Hz
CMRR	> 100 dB @ DC, 50 Hz/60 Hz; $R_s = 1$ k Ω
Input impedance	AutoTest™ Lo-Z V dc: 833 k Ω (4.2 k Ω when displaying AUTO), 90 pF nom.
V dc AutoTest™ threshold	> +1.2 V dc or < -0.6 V dc nominal (Hi-Z V dc only)
AC Voltage	
Range	Accuracy
50 Hz - 60 Hz	
6.000 V, 60.00 V, 600 V	\pm (1.5 % + 5 dgt)
CMRR	> 60 dB @ dc to 60 Hz, $R_s = 1$ k Ω
Input impedance	AutoTest™ Lo-Z V ac: 160 k Ω , 160 pF nominal
Hi-Z ACV	5 M Ω , 90 pF nominal
ACV AutoTest™ threshold	> 1.5 V ac (50 Hz/60 Hz) nominal
Capacitance	
Range¹	Accuracy²
100.0 nF, 1000 nF, 10.0 μ F, 100.0 μ F, 2000 μ F ³	\pm (3.5 % + 6 dgt)
¹ Accuracy below 50 nF is not specified	
² Accuracies with film capacitor or better	
³ Updates > 1 minute on large values	
⁴ Specified with battery voltage above 2.8 V (half full battery). Accuracy decreases gradually to 12% at low battery warning voltage of approx. 2.4 V.	
Resistance	
Range	Accuracy
600.0 Ω	\pm (2.0 % + 6 dgt) ²
6.000 k Ω	\pm (1.2 % + 6 dgt) ²
60.00 k Ω , 600.0 k Ω	\pm (1.0 % + 4 dgt)
6.000 M Ω	\pm (2.0 % + 4 dgt)
Open circuit voltage	0.4 V dc typical

¹AutoTest™ is for 6.000 k Ω ~ 6.000 M Ω ranges

²Add 40 dgt to specified accuracy while reading is below 20 % of range

PM 55

The compact precision DMM with AutoTest™ and VolTect™



Electrical noise or intense electromagnetic fields in the vicinity of the equipment may disturb the measurement circuit. Measuring instruments will also respond to unwanted signals that may be present within the measurement circuit. Users should exercise care and take appropriate precautions to avoid misleading results when making measurements in the presence of electronic interference.

PM 55 Specifications *cont.*

Frequency		
Range	Accuracy	Specified at
10.00 Hz - 30.00 kHz ^{1, 2}	± (0.5 % + 4 dgt)	< 2 0 V Sine-rms
10.00 Hz - 999.9 Hz	± (0.5 % + 4 dgt)	< 600 V Sine-rms
¹ Sensitivity (Sine-rms): Hz in Auto-V (position: > 3 V		
² Line-level Hz in V position: @6.000 V ac range: > 3 V; @60.00 V ac range: > 6 V; @600.0 V ac range: > 60 V		
DC µA Current		
Range	Accuracy	Burden voltage
400.0 µA	± (1.5 % + 3 dgt)	6 mV/µA
2000 µA	± (1.2 % + 3 dgt)	6 mV/µA
AC µA Current		
Range	Accuracy	Burden voltage
400.0 µA	± (2.0 % + 3 dgt)	6 mV/µA
2000 µA	± (1.5 % + 3 dgt)	6 mV/µA
VolTect™		
Typical voltage	Bar graph indication	
15 V to 55 V	-	
30 V to 85 V	--	
55 V to 145 V	---	
85 V to 190 V	----	
above 120 V	-----	
Indication	Bar graph segments & audible beep tones proportional to field strength	
Detection frequency	50/60 Hz	
Detection antenna	Top left corner of the meter	
Audible Continuity Tester (600 Ω range)		
Open circuit voltage	0.4 V dc typical	
Audible threshold	50 Ω to 300 Ω	
Diode Test		
Diode test current	0.48 mA	
Open circuit voltage	< 1.6 V dc	
General Specifications		
Display and update rate	3-5/6 digits 6000 counts; Updates 5 per second nominal	
Operating temperature	0 °C - 40 °C	
Relative humidity	Max. 80 % R.H. up to 31 °C, decreasing linearly to 50 % R.H. at 40 °C	
Altitude	Operating below 2000 m	
Storage temperature	-20 °C ~ 60 °C, < 80 % R.H. (with battery removed)	
Temperature coefficient	Nominal 0.15 x (specified accuracy)/ °C @ (0 °C ~ 18 °C or 28 °C ~ 40 °C), or otherwise specified	
Sensing	Average sensing	
Overload protection	600 V dc and V ac rms	
Low battery	Below approx. 2.4 V	
Power supply	3 V standard button battery x 1 (IEC-CR2032; ANSI-NEDA-5004LC)	
Power consumption (typical)	6 mA for voltage functions on Auto-V W position & 2 mA for other functions	
Automatic Power Off (APO) timing	Idle for 3 minutes	
APO consumption (typical)	2.2 µA	
Dimension/Weight	L 113 mm x W 53 mm x H 10.2 mm (4.4 x 2.1 x 0.4 in)/Approx. 78 gm (3 oz)	
Special features	AutoTect™ (Automatic V & Ω selection) and VolTect™ (Electric Field Detection)	
Agency approvals	CE, cULus	
Safety	Meets IEC61010-1, UL61010B-1, CAN/CSA-C22.2 No. 1010.1-92, CAT II 600 V and CAT III 300 V, Pollution Degree 2, Class 2	
E.M.C.	Meets EN61326	
Included Accessories		

WARRANTY

