

Digitale Handmultimeter

Fluke 27 Multimeter

| Specifications | |
|----------------|---|
| Voltage DC | Range and Resolution: 320.0 mV, 3.200V, 32.00V, 320.0V, 1000V Best Accuracy: $\pm(0.1\%+1)$ |
| Voltage AC | Range and Resolution: 320.0 mV, 3.200V, 32.00V, 320.0V, 1000V Best Accuracy: $\pm(0.5\%+3)$ |
| Current DC | Range and Resolution: 320.0 μ A, 3200 μ A, 32.00 mA, 320.0 mA, 10.00A Best Accuracy: $\pm(0.75\%+2)$ |
| Current AC | Range and Resolution: 320.0 μ A, 3200 μ A, 32.00 mA, 320.0 mA, 10.00A Best Accuracy: $\pm(1.5\%+2)$ |
| Resistance | Range and Resolution: 320.0 Ω , 3.200 k Ω , 32.00 k Ω , 320.0 k Ω , 3.200 M Ω , 32.00 M Ω Best Accuracy: $\pm(0.2\%+1)$ |
| Conductance | Range and Resolution: 32.00 nS Best Accuracy: $\pm(2\%+10)$ |
| Battery Life | Typically over 1000 hours (alkaline) |
| Size | 203 mm L x 95 mm W x 56 mm D (8" L x 3.75" W x 2.2" D) |
| Weight | 0.75 kg (1.6 lb) |
| Warranty | Lifetime Limited; One year calibration interval |



Features at a Glance:

- Digital Display/Counts 3200
- Analog Bar Graph/Segments 31
- AC & DC Voltage
- Resistance
- Diode Test
- Fast Continuity Beeper
- Auto and Manual Ranging
- Automatic TouchHold®
- Superior EMI Shielding
- Operates from -15°C to 55°C (5°F to 131°F) and 95% Relative Humidity
- Rugged, O-Ring Sealed Case
- Built-in Tilt-Bail Hanger
- Meets Military Shock, Vibration and Water-Proof Requirements
- Min/Max and Relative Mode
- Lifetime Warranty