


PEWA Messtechnik GmbH

Weidenweg 21 58239 Schwerte

Tel.: 02304-96109-0 Fax: 02304-96109-88 E-Mail: info@pewa.de Homepage : www.pewa .de

Model 3430 Adapter – Binding Post To **BNC Male**



FEATURES:

Permits single banana plug to be used with equipment having a BNC female.

MATERIALS:

Upper Conn: Insulated Binding Post

Material: Binding Post Body – Brass per QQ-B-626, Allow 360, ¹/₂ Hard.

Finish: Nickel plated per QQ-N-290, Class 2, 200/300 microinches.

Insulation: Polycarbonate.

Color: See Ordering Information.

Lower Conn.: BNC Male

Finish: Body and fittings - Tarnish Resistant. Nominal Impedance: 50 Ohms.

RATINGS:

6/9/99

SY/EH/LS

Operating Temp.: +115° C. (+239° F.) Max. Operating Voltage: Hand-held Testing: 30VAC/60VDC Max. Hands free Testing in Controlled Voltage Environments: 500 VRMS Max.

ORDERING INFORMATION: Model 3430-*

* = Color, -0 Black, -2 Red

Ordering Example: 3430-2 Color is Red

All dimensions are in inches. Tolerances (except noted): $xx = \pm .02^{\circ}$ (.51 mm), $xxx = \pm .005^{\circ}$ (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060 S:\Engineering \Release \DataSheets \FlukeDataSheet\d3430 1 01.doc

PomonaACCESS 90575 (800) 444-6785 or (425) 446-6010 More drawings available at www.pomonaelectronics.com Page 1 of 1