


# **Model 3542 Insulated Panel Mount Pin** Tip Jack CE



#### **FEATURES:**

Accepts .080 pin tip plugs Mounts in panels up to .250" thick.

## **MATERIAL:**

Insulation – Polycarbonate - Molded to pin tip jack body Lockwasher, #8 Internal Tooth – Nickel plated Steel Hex Nut #8-32 – Nickel plated Brass Pin Tip Jack Body: Gold plated Brass



#### **RATINGS:**

Operating Voltage: Hands free usage in controlled voltage environments: 1500 Vrms maximum. For CE compliance: not

intended for hand-held use at voltages above 33 Vrms/70 Vdc.

Current: 5 Amps

Operating Temperature: +239°F (+115°C). Max.

### **ORDERING INFORMATION:** Model 3542-Color (sold in packages of 10)

Colors =: 0 (Black), 1 (Brown), 2 (Red), 3 (Orange), 4 (Yellow), 5 (Green), 6 (Blue), 7 (Violet), 8 (Gray), 9 (White)

Ordering Example: 3542-2 (Red)

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (.51 mm),  $.xxx = \pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technical support@pomonatest.com) For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com

Rev: 100 D1093949