



## **MATERIALS:**

Connector:

Body: Tarnish Resistant Plating, Center Contact: Gold Plated Beryllium Copper Shielded Housing: Die cast aluminum, Alloy A380 or A384 Cover: .040 thick aluminum alloy 1100-H14 Screws: Steel. 4 each 2-32 x <sup>1</sup>/<sub>4</sub>" pan head, self-tapping Finish: Shielded Housing – None Cover – Clear anodized Screws – Zinc per ASTM B633-85, Type II (bright blue)

## **RATINGS:**

Operating Temperature: -55°C to +150°C

## **ORDERING INFORMATION:** Model 3754

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02^{\circ\circ}$  (,51 mm),  $.xxx = \pm .005^{\circ\circ}$  (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. Made in USA

6/9/99 Sales: 800-490-2361 Fax: 888-403-3360 SY/EH/LS <u>Technical Assistance: 800-241-2060</u> S:\Engineering\Release\DataSheets\FlukeDataSheett\d3754\_1\_01.doc PomonaACCESS 90205 (800) 444-6785 or (425) 446-6010 More drawings available at www.pomonaelectronics.com Page 1 of 1