

PEWA Messtechnik GmbH

Weidenweg 21 58239 Schwerte

Tel.: 02304-96109-0 Fax: 02304-96109-88 E-Mail: info@pewa.de Homepage: www.pewa.de

## 

## **FEATURES:**

- ✓ Kit contains the most frequently need adapters to fit between instruments or equipment with type N and DIN connectors.
- ✓ Peak power rating of 40 kW compared to 10kW for type N.
- ✓ Foam lined zipper case keeps adapters handy for instant use.
- ✓ Reduced intermodulation generation.
- ✓ Improved VSWR.
- ✓ Greater resistance to environmental forces.
- Coupling mechanism provides higher contact pressure and full circumference contact.
- ✓ Longer, more durable and long-term reliable conductors.
- ✓ Longer service life under harsh conditions.

## **RATINGS:**


Impedance: 50 Ohms


Frequency Range: DC - 7.5 GHz

Insertion Loss: - .01 dB

VSWR (Max): < 1.10:1 @ DC - 7.5 GHz

Third Order IM: -dBc > -150 dBc





| CONTENTS:             | Model: |
|-----------------------|--------|
| Type N (m) to DIN (m) | 6256   |
| Type N (f) to DIN (m) | 6257   |
| Type N (m) to DIN (f) | 6259   |
| Type N (f) to DIN (f) | 6260   |
| DIN (f-f)             |        |
| Right Angle (m-f)     |        |

## **MATERIALS:**

Pomona's 7/16 DIN adapters are made in the US and feature silver plated outer shells, Teflon insulation and silver plated, Beryllium Copper female and brass male center contacts.

**ORDERING INFORMATION:** Model 6254

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (,51 mm),  $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Rev: 100 D1094423