


## Model 6469 SMD Microtip Test Probe Set



### FEATURES:

- Replaceable tip probe set with spring loaded pogo pin triple point SMD Microtip included. (Other tips are available, see model 6475)
- Designed for most DMM's including Fluke, Wavetek, Metroman, Amprobe, and others with safety sheathed banana jacks
- Thermoplastic elastomer outer coat provides comfortable grip and flexible strain relief
- Tough polymer undercoat provides strength
- Probe body and banana plug are molded directly to the wire for robust pull strength
- Wire is a high strand count silicone wire for extreme flexibility and high temperature resistance
- Wear indication with double insulated (dual extruded) silicone leads shows white inner layer for increased safety
- Banana plug spring is nickel plated Beryllium Copper for long insertion life



### MATERIALS:

#### Probe Body:

Outer Insulation: Santoprene® rubber, color: gray

Inner Insulation: Polypropylene, color: one black, one red

Tip: Gold plated SMD Microtip pogo-pin

Wire: 18 AWG, 192 x 41 bare copper, Silicone Insulation, O.D. 0.144" (3,66mm)

Banana Plug: Brass, nickel plated

Spring – Beryllium Copper, nickel plated

Plug Insulation: Polypropylene, color: one black, one red

### RATINGS:

IEC 61010-031

Operating Voltage: CAT II 1000 V

Current: 5 Amperes

### ORDERING INFORMATION

Model 6469

Includes a set of one black and one red test lead with two replaceable tips

**USA:** Sales: 800-490-2361  
Technical Support: [technicalsupport@pomonatest.com](mailto:technicalsupport@pomonatest.com)  
Fax: 425-446-5844  
**Europe:** 31-(0) 40 2675 150 **International:** 425-446-5500  
**Where to Buy:** [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.