

Model 6733, 6734 Test Lead Wire with Silicone or PVC Insulation

Features:

- ✓ Same wire as used with the Pomona test leads and patch cords.
- ✓ Make your own “Extra Long” test leads, jumpers or patch cords.
- ✓ Fits Pomona “Do-It-Yourself” banana plugs and jacks.
- ✓ High temperature and voltage ratings.
- ✓ Silicone insulation with high wire strand count allows for superb flexibility.
- ✓ Wire will comply with International Safety Standard CAT III, IEC1010 requirements when correctly terminated with other components designed to meet CAT III, IEC1010 requirements.



Specifications:	6733	6734
Insulation:	Silicone	PVC
Length:	50 FT (15,2 meters)	50 FT (15,2 meters)
Wire size:	18 AWG	18 AWG
Wire:	65 X 36 tinned copper	65 X 36 tinned copper
Diameter (OD):	.144" (3,60mm)	.144" (3,60mm)
Temperature:	-58 to +302 F (-50 to +150 C)	-4 to +221 F (-20 to +105 C)
Wire Rated Voltage:	10,000 DC *	5,000 DC *
Current:	20 A	15 A
Ordering Information:		
Black Wire:	6733-0	6734-0
Red Wire:	6733-2	6734-2
* Hands free testing in controlled voltage environment: <i>For CE compliance:</i> not intended for hand held use at voltages above 33 Vrms / 70 Vdc.		

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060
For “Where to Buy” information, visit the Pomona web site at www.pomonaelectronics.com