

PEWA Messtechnik GmbH

Weidenweg 21 58239 Schwerte

Tel.: 02304-96109-0 Fax: 02304-96109-88 E-Mail: info@pewa.de Homepage: www.pewa.de


Model 72937 IEC Insulated BNC (M) to two 4 mm banana jacks


(19 mm + 0.2) 0.748" + 0.008-0.020



Features

- IEC Insulated BNC (M) to two 4mm banana jacks.
- Adapter converts test instrument safety banana leads to BNC configuration for added shielding and safety.
- Rating: 500V Cat I, 150V Cat II





Materials

Connector body: Nickel plated BrassCenter Contact: Gold Plated Brass

Dielectric: White PTFEInsulation: Polyamide

• Banana Jack: Nickel plated Brass

Specifications

Max Current	ЗА
Max Voltage	500V CAT I, 150V CATII

Ordering Information

Model: 72937

USA: Sales: 800-490-2361 Fax: 888-403-3360 **Europe:** 31-(0) 40 2675 150 **International**: 425-446-5500

e-mail: technicalsupport@pomonatest.com
Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02$ " (,51 mm), $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.