Weidenweg 21 58239 Schwerte Tel.: 02304-96109-0 Fax: 02304-96109-88 E-Mail: info@pewa.de

Model 72996 SMB JACK STRAIGHT PCB RECEPTACLE



Model 72996 SMB JACK STRAIGHT PCB RECEPTACLE

(6,4mm X 6,4mm) .25" × .25" (11.4mm) 0,1mr .004" (3.9mm)5 (Ø1.2mm) (6.3mm).15" .05″ 25" (ø1mm) $(5.1 \text{mm} \pm 0.1 \text{mm})$.05"

Snap-on coupling and small size for fast connect and disconnect.

Features

- DC 4 GHz bandwidth.
- Meets MIL-C-39012, IEC 60169-1Q, BS9210N0007, NFC93650, CECC 22130.
- Small size and durability for RF coaxial applications.
- Precision machined and gold-plated for low loss.

Materials

- Body is machined brass with gold plating.
- Center contacts Plug is gold plated brass and Jack is gold plated beryllium copper.
- High quality PTFE insulators.
- Crimp Ferrules are nickel plated copper.
- Silicone rubber gaskets.

Ordering Information

Model: 72996

Description: SMB JACK STRAIGHT PCB RECEPTACLE

USA: Sales: 800-490-2361

Technical Support: technicalsupport@pomonatest.com

Fax: 425-446-5844

Europe: 31-(0) 40 2675 150 **International**: 425-446-5500

Where to Buy: www.pomonaelectronics.com

Specifications

<u> </u>	
Impedance	50 Ω
Frequency Range	DC - 4 GHz
VSWR	1.3 max
Working Voltage	250 Vrms max.
Dielectric withstand voltage	750 Vrms
Center / Outer contact resistance	6 / 1 mΩ
Number of insertions	500 cycles min.
Insulation resistance	1,000 MΩ min.
Temperature Range	-65° C to 165° C, -85° F to 329° F

All dimensions are in inches. Tolerances (except noted): $xx = \pm .02$ " (.51 mm), $.xxx = \pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. D2003433 REV 001