

PEWA Messtechnik GmbH

Weidenweg 21 58239 Schwerte

Telefon: +49 (0) 2304-96109-0 Telefax: +49 (0) 2304-96109-88 eMail: info@pewa.de Homepage: www.pewa.de



VPS200-R Voltage Probe Set, Red 200 MHz (one red)

Double insulated safety designed probe for ScopeMeter190 series.



- Each probe set includes
- 600 V CAT III / 1000 V CAT II rated
- 10:1 Voltage Probe,
- Hook Clip for Probe Tip, 4 mm Test Probe for Probe,
- Ground Lead with Hook Clip,
- Ground Lead with Mini Alligator,
- The red Probe Set also includes a
- 30 V CAT II rated
- Ground Spring for Probe Tip.
- Attenuation: 10x
 Randwidth: 200 MH
- Bandwidth: 200 MHz
- Max. Input Voltage: 1000 V
- Max. Voltage to ground: 600 V CAT III 1000 V CAT II per IEC / EN61010-2-031
- Input Resistance: 10 MohmInput Capacitance: 14 pF
- Compensation range: 10 to 22 pF
- Cable Length: 1.2 m

VPS200-G Voltage Probe Set, Gray 200 MHz (one gray)

Double insulated safety designed probe for ScopeMeter190 series.



- · Each probe set includes
- 600 V CAT III / 1000 V CAT II rated
- 10:1 Voltage Probe,
- Hook Clip for Probe Tip, 4-mm Test Probe for Probe,
- · Ground Lead with Hook Clip,
- Ground Lead with Mini Alligator,
- The red Probe Set also includes a
- 30 V CAT II rated Ground Spring for Probe Tip.
- Attenuation: 10x
- Bandwidth: 200 MHz
- Max. Input Voltage: 1000 V
- Max. Voltage to ground: 600 V CAT III 1000 V CAT II per IEC / EN61010-031
- Input Resistance: 10 Mohm
- Input Capacitance: 14 pF
- Compensation range: 10 to 22 pF
- Cable Length: 1.2 m

