



Nitrite, HR

- Simple to operate
- Rugged housing for field use
- Long battery life

Nitrites are an intermediate product in the nitrogen cycle and are produced during ammonia oxidation with water, or even originate in industrial waste directly. They must not be present in drinking water. Nitrites can be harmful to aquatic organisms even in low concentrations and for this reason, they are closely monitored in aquaculture facilities. In cooling towers, however, an adequate amount of nitrites is necessary to prevent corrosion. In high concentrations, they can be harmful to environment and to man. They are, therefore, normally monitored to verify the quality of water for domestic use, as well as lakes and ponds. HI 93707 and HI 93708 show the nitrite concentration directly in the 0.00 to 0.35 mg/L and 0 to 150 mg/L ranges, with increments of 0.01 mg/L and 1 mg/L, respectively.

HI 93708 is supplied complete with 2 cuvetts, battery and instructions.

PEWA Messtechnik GmbH

Weidenweg 21
58239 Schwerte

Telefon: +49 (0) 2304-96109-0

Telefax: +49 (0) 2304-96109-88

eMail: info@pewa.de

Homepage: www.pewa.de



Available Accessories:

- HI 710009** Blue rubber boot
- HI 710010** Orange rubber boot
- HI 731318** Tissue for wiping cuvetts (4 pcs)
- HI 731321** Spare measurement cuvetts (4 pcs)
- HI 93703-50** Cuvet cleaning solution (230 mL)q
- HI 731325** Cuvet cap (4 pcs)
- HI 93708-01** Reagent kit for 100 tests
- HI 93708-03** Reagent kit for 300 tests

Specifications:

Range	0 to 150 mg/L
Resolution	1 mg/L
Accuracy (@20°C/68°F)	±4 mg/L ±4% Full Scale
Typical EMC Deviation	±1 mg/L
Light Source	Light Emitting Diode
Light Life	Life of the Instrument
Light Detector	Silicon Photocell
Battery Type / Life	9 Volt Battery/ Approximately 300 tests
Environment	32 to 122°F (0 to 50°C); RH 95%
Dimensions	7.1 x 3.3 x 1.8" (180 x 83 x 46mm)
Weight	10 oz. (290 grams)