

PFWA Messtechnik GmhH Weidenweg 21 58239 Schwerte Telefon: +49 (0) 2304-96109- 0 Telefax: +49 (0) 2304-96109-88 eMail: info@pewa.de Homepage: www.pewa.de

Manganese, LR

- Ouick and accurate
- PAN method for measuring Manganese
- Battery life good for more than 300 tests

Manganese is one of the most common metals present in nature and is used in many industrial applications, for example, in the production of fertilizers and in the pharmaceutical industry. Manganese salts are also used in iron alloys (steel manufacturing) and noniron alloys as it improves their corrosion resistance and hardness. Manganese is not considered to be dangerous, but high concentrations of this metal in water will result in change of taste and smell. In industry, manganese can produce corrosion and incrustations to pipes when found in high concentrations. HI 93709 and HI 93748 are portable microprocessor meters that determine the concentration of manganese in water at the touch of a button, and are ideal for field applications and monitoring.

HI 93748 is supplied complete with 2 cuvets, battery and instructions.

Available Accessories:

HI 710009 Blue rubber boot

HI 710010 Orange rubber boot

HI 731318 Tissue for wiping cuvets (4 pcs)

HI 731321 Spare measurement cuvets (4 pcs)

HI 93703-50 Cuvet cleaning solution (230 mL)

HI 731325 Cuvet cap (4 pcs)

HI 93748-01 Reagent kit for 50 tests

HI 93748-03 Reagent kit for 150 tests

Specifications:

Range 0 to 300 µg/L

Resolution 1 µg/L

Accuracy (@20°C/68°F) $\pm 2 \mu g/L \pm 3\%$ reading

Typical EMC Deviation ±1 µg/L

Light Source Light Emitting Diode @ 555 nm

Light Life Life of the instrument Light Detector Siliicon Photocell

Battery Type / Life 1 x 9V/ approximately 40 hours of continuous use

Environment 0 to 50°C (32 to 122°F); RH 95% **Dimensions** 180 x 83 x 46 mm (7.1 x 3.3 x 1.8")

Weight 290 g (10 oz.)