

Sorry,  
No Image  
Available

HI 6493005

## AmpHel ORP Electrode with Pin, cloth junction and 5 m

[Click to Buy](#)



AmpHel ORP electrode with gold pin, cloth junction and 5 m cable.

- Strong signal up to 75 meters (246')
- Low noise coaxial cables are no longer required
- Measurements in unclean samples and high humidity conditions
- Models with external replaceable battery, for longer electrode life
- Glass sensor for specific applications

Due to the high resistance of the glass membrane, conventional electrodes require an impedance measurement system. Inadequate insulation of the connectors and result in erroneous readings due to leakage or noise. For conventional electrode lead is therefore limited to typically less than 15-20 meters. HANNA AmpHel® incorporate a miniaturized amplifier which resolves most of the problems associated with high impedance signals. The amplifier circuitry is located right on top of the electrode and is completely sealed. As a result, a strong, low impedance signal is emitted. Ordinary connectors with long unshielded cables can be used. This breakthrough technology provides a stable signal for industrial monitoring as well as a major reduction in low noise coaxial cable costs. In some cases, the need for a transmitter is also eliminated, resulting in further cost reductions.

For those applications that have been proven particularly hostile to electrodes, HANNA has developed four types of specialized glass. First is an extremely durable sensor for general purpose and industrial use. This glass can withstand the stress of deep-sea applications. The remaining types of electrode glass allow continuous monitoring in highly acidic and alkaline environments.

solutions containing fluoride ions, as well as high or low temperature processes without significantly reducing the useful life of the electrode.

Electrode body material is glass or PEI, while the junction is cloth or PTFE.

Specifications	Dimensions
<b>Body</b>	PEI
<b>Junction</b>	cloth
<b>Electrolyte</b>	gel
<b>Pin Type</b>	gold
<b>Temperature</b>	-5 to 80°C
<b>Max Pressure</b>	3 bar (43.5 psi)
<b>Connection</b>	BNC
<b>Cable</b>	5 m
<b>Battery</b>	replaceable