



According to Regulation (EC) No. 1907/2006

Revision Date: 2008-12-01

Reason for Revision: REACH Compliance and General Update

SECTION 1: IDENTIFICATION OF THE PRODUCT AND COMPANY

Product Name: HI 93763B-0 Molybdovanadate Reagent Additional Product Codes:

Application: Determination of Phosphorus in Water Samples

Company Information (USA): Hanna Instruments, Inc.

584 Park East Dr, Woonsocket, Rhode Island, USA 02895

Technical Service Contact Information: 1-800-426-6287 (8:30AM - 5:00PM ET)

+1-401-766-4260 (8:30AM - 5:00PM ET)

USA Emergency Contact Information: 1-800-424-9300 (Chemtrec 24Hr. Emergency)

International Emergency Contact Information: +1-703-527-3887 (Chemtrec 24Hr. Emergency)

E-mail Address: tech@hannainst.com

SECTION 2: HAZARD IDENTIFICATION

Causes severe burns.

SECTION 3: COMPOSITION AND COMPONENT INFORMATION

Component: Ammonium Metavanadate Ammonium Molybdate Sulfuric Acid

Tetrahydrate 232-261-3 231-639-5

234-320-9

CAS-No.: 7803-55-6 7664-93-9

Hazard: T C

Phrases: R: 23/25-37/38-41 R: 35

Content: > 0.1% - < 3% > 35% - < 51%

> 1% - < 5%

SECTION 4: FIRST AID MEASURES

After Inhalation: Remove to fresh air. Immediately summon doctor.

After Skin Contact: Wash effected area with plenty of water. Immediately remove contaminated clothing.

After Eye Contact: Rinse out immediately with plenty of water for at least 10 minutes and seek medical advice.

R: 36/37/38-52/53

After Swallowing: Drink plenty of water (if necessary several liters), avoid vomiting (risk of

perforation!). Immediately seek medical advice. Do not attempt to neutralize.

General Information: Remove contaminated, soaked clothing immediately and dispose of safely.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Water spray, Carbon Dioxide, Dry Chemical Powder, Appropriate Foam.

Special Risks:

Development of hazardous combustion gases or vapors possible in the event of fire. Hydrogen may form upon contact with metals (danger of explosion!). The following may develop in event of fire: Sulfur Oxides, Ammonia, Nitrogen Oxides.

Special Protective Equipment:

Do not stay in dangerous zone without suitable chemical protection clothing and self-contained breathing apparatus.

Additional Information:

Product itself is non-combustible. Cool container with spray water from a safe distance. Contain escaping vapors with water.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations



According to Regulation (EC) No. 1907/2006

ACCIDENTAL RELEASE MEASURES **SECTION 6:**

Personal Precautions:

Avoid substance contact. Ensure supply of fresh air in enclosed rooms. Take up with liquid-absorbent material. Clean up affected area and dispose according to local regulation.

Environmental Precautions:

Do not discharge into the drains/surface waters/groundwater.

Additional Notes:

Render harmless: neutralize with diluted sodium hydroxide solution or by throwing on lime, lime sand, or sodium carbonate.

HANDLING AND STORAGE **SECTION 7:**

Handling: Storage:

Avoid generation of vapors/aerosols. Work under hood. Do not inhale substance.

Tightly closed. In a well-ventilated place at +15 to +25 °C. Accessible only for authorized persons.

EXPOSURE CONTROL/PERSONAL PROTECTION SECTION 8:

Ingredients:

SULFURIC ACID **EXPOSURE LIMITS - GERMANY** Source Value Type TRGS 900 OEL 1 mg/m³

EXPOSURE LIMITS - DENMARK

Source Type Value OEL TWA 1 mg/m³

Molybdenum, soluble compounds (as Mo)

MAK 5 mg/m³

Engineering:

Maintain general industrial hygiene practice.

Personal Protective Equipment:

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled.

Respiratory Protection: **Protective Gloves:** Eye Protection:

Rubber or plastic

Required when vapors/aerosols are generated. Work under hood. Do not

inhale substance.

Industrial Hygiene:

Change contaminated clothing. Wash hands after working with substance.

SECTION 9: PHYSICAL/CHEMICAL PROPERTIES

Pale yellow liquid Appearance: Odor: Odorless Density at 20° C: ~ 1.3 g/cm3

Melting Point: Boiling Point: ND Solubility: ND Soluble

(development of heat)

Goggles or face mask

pH at 20° C: Strongly acid Explosion Limit: NA Flash Point: NA

Thermal Decomp.: NA



According to Regulation (EC) No. 1907/2006

SECTION 10: STABILITY AND REACTIVITY

Conditions to be Avoided:

Heating (decomposition).

Hazardous Polymerization:

Will not occur.

Further Information:

Hygroscopic. Has a corrosive effect. Incompatible with metals, animal and vegetable tissues.

Hazardous Decomposition Products:

In the event of fire: See section 5.

Substances to be Avoided:

Water, alkali metals, alkali compounds, ammonia, alkaline earth compounds, alkalis, acids, alkaline earth metals, metals, metal alloys, phosphorus oxides, phosphorus, hydrides, halogen-halogen compounds, oxyhalogenic compounds, permanganates, nitrates, carbides, combustible substances, organic solvents, acetylidene, nitriles, nitrides, organic nitro compounds, anilines, peroxides, picrates, lithium silicide

SECTION 11: TOXICOLOGICAL INFORMATION

Quantitative data on the toxicity of this product is not available.

Sulfuric Acid: acute toxicity:

LD50 (oral, rat): 2140 mg/kg (Using 25 % solution).

LC50 (inhalation, rat): 510 mg/m³ /2 h (calculated on the pure substance).

Ammonium Metavanadate: acute toxicity:

LD50 (oral, rat): 169 mg/kg. LD50 (dermal, rat): > 2500 mg/kg. LC50 (inhalation, rat): 2500 mg/m³ /4 h.

In Case of Inhalation: After inhalation of aerosols: damage to the affected mucous membranes.

In Case of Skin Contact: Severe burns with formation of scabs.

In Case of Eye Contact: Burns, corneal lesion.

In Case of Ingestion: Severe pain (risk of perforation!), nausea, vomiting and diarrhea.

Further Data: Systemic effects: applicable to partial component(s): Vanadium compounds generally cause irritations after eye

and skin contact and mucosal irritations, coughing and dyspnoea after inhalation. After absorption of toxic quantities symptoms are: changes in the blood picture, loss of weight, cardiovascular complaints. Molybdenum (VI) acute intoxication symptoms are: diarrhea, anemia, fatigue. Toxic effect on liver and kidneys after high doses. Further hazardous properties cannot be excluded. The product should be handled with the usual care when

dealing with chemicals.

SECTION 12: ECOLOGICAL INFORMATION

Quantitative data on the ecological effect of this product is not available. Biological effects: harmful effect on aquatic organisms. Harmful effect due to pH shift. Toxic effect on fish and algae. Caustic even in diluted form. Endangers drinking-water supplies if allowed to enter soil and/or waters in large quantities. Neutralization possible in waste water treatment plants.

Further Data: APPLICABLE TO PARTIAL COMPONENT:

The following applies to vanadium compounds in general: toxic for aquatic organisms: LD50 from 4.8 mg/L up in soft water,

from 30 mg/L up in hard water.

The following applies to molybdenum compounds in general: biological effects: fish: lethal from 25 mg/L up; algae: Sc.

quadricauda toxic from 54 mg/L up; protozoa: Microregma toxic from 27 mg/L up.

The following applies to ammonium ions in general: biological effects: fish: toxic as from 0.3 mg/L; nourishment for fish: toxic as from 0.3 mg/L. Depending on the concentration, nitrogen compounds may contribute to the eutrophication of drinking

water supplies.

DO NOT ALLOW TO ENTER WATERS, WASTE WATERS, OR SOIL!

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Chemical residues are generally classified as special waste and thus covered by local regulations. Contact local

authorities or disposal companies for advice. Handle contaminated packaging in the same way as the substance itself.

SECTION 14: TRANSPORTATION INFORMATION

Land: Sea: Air:

ADR/RID: 9, II IMDG: 9/UN 3316/PG II ICAO/IATA: 9/UN 3316/PG II UN-No. : 3316 Name : CHEMICAL KIT Name: CHEMICAL KIT

Name: CHEMICAL KIT

Transport data applies to the COMPLETE KIT!



NA: Not Applicable ND: Not Determined

According to Regulation (EC) No. 1907/2006

SECTION 15: REGULATORY INFORMATION

Labeling according to EC Directives:

Symbol: C: Corrosive

R-phrases: 35: Causes severe burns.

S-phrases: 26-30-36/37/39-45: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Never add water to this product. Wear suitable protective clothing, gloves and eye/face protection. In case of accident

or if you feel unwell, seek medical advice immediately (show the label where possible).

Revision Date:

Contains: Sulfuric acid

SECTION 16: OTHER INFORMATION

Text of R-phrases under Section 3 Revision Information Legend

23/25: Toxic by inhalation and if swallowed.

35: Causes severe burns.

36/37/38: Irritating to eyes, respiratory system and skin.

52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Supersedes edition of: 2008-01-03

Reason for revision: **REACH Compliance and General Update**

2008-12-01

THE INFORMATION CONTAINED HEREIN IS BASED ON THE PRESENT STATE OF OUR KNOWLEDGE. IT CHARACTERIZES THE PRODUCT WITH REGARD TO THE APPROPRIATE SAFETY PRECAUTIONS. IT DOES NOT REPRESENT A GUARANTEE OF THE PROPERTIES OF THE PRODUCT.