



HI 96718

Iodine Portable Photometer



PEWA
Messtechnik GmbH

Weidenweg 21
58239 Schwerte

Tel.: 02304-96109-0
Fax: 02304-96109-88
E-Mail: info@pewa.de
Homepage: www.pewa.de

- CAL CHECK™
- User calibration
- Certified calibration and verification standards
- BEPS (Battery Error Prevention System)
- TIMER function
- Auto shut-off
- GLP Features

The disinfectant properties of Iodine have led to its use as an alternative to chlorine and bromine. Unlike chlorinated pools, water treated with iodine decreases eye irritation among swimmers, and provides a level of disinfection more stable to adverse conditions.

However, its toxic and corrosive properties and the difficulties of dissolving it in water has limited its widespread acceptance. One of its most common applications is in poultry industry process water.

HI 96718 uses an exclusive positive-locking system to ensure that the cuvette is in the same position every time it is placed into the measurement cell. It is designed to fit a cuvette with a larger neck making it easier to add both sample and reagents. The cuvette is made from special optical glass to obtain best results.

The HI 96718 measures the Iodine content in water samples in the 0.0 to 12.5 mg/L (ppm) range. The method is an adaptation of the Standard Methods for the Examination of Water and Wastewater, 18th edition, DPD method.

Order Information:

HI 96718 is supplied with sample cuvettes with caps (2), 9V battery and instruction manual.

HI 96718C includes HI 96718 photometer, sample cuvettes with caps (2 ea.), 9V battery, scissors, cloth for wiping cuvettes, instrument quality certificate, instruction manual and rigid carrying case.

Specifications	Accessories	Downloads
----------------	-------------	-----------

Range	0.0 to 12.5 mg/L	
Resolution	0.1 mg/L	
Accuracy	±0.1 mg/L ±5% of reading @ 25°C	
Light Source	Tungsten lamp	
Light Detector	Silicon photocell with narrow band interference filter @ 525 nm	
Method	adaptation of the Standard Methods for the Examination of Water and Wastewater, 18th edition, DPD method	
Environment	0 to 50°C (32 to 122°F); max 95% RH non-condensing	
Power Supply	9V battery	

Auto-Shut off	after ten minutes of non-use in measurement mode; after one hour of non-use in calibration mode; with last reading reminder
Dimensions	192 x 104 x 69 mm (7.6 x 4.1 x 2.7")
Weight	360 g (12.7 oz.)