ordering

- **HI 9829 is supplied complete with your choice of probe and probe maintenance kit.**

  This kit includes HI 7042S (electrolyte solution for DO sensor), (5) O-rings for DO sensor, a small brush, (5) O-rings for probe and a syringe with grease to lubricate the O-rings.

ORDERING INFORMATION

Most **HI 9829 configurations** are supplied with multisensor probe, HI 9828-25 quick calibration standard solution (500 mL), probe maintenance kit, rechargeable Ni-MH batteries (4), power adapter & cable, car 12 V accessory outlet adapter, HI 7698281 USB interface cable, HI 929829 Windows® compatible software, instruction manual and rugged carrying case. Choose your configuration below:

HI 9829-01	Standard meter without probe, 115VAC
HI 9829-02	Standard meter without probe, 230VAC
HI 98290-01	HI 9829 with GPS, 115VAC
HI 98290-02	HI 9829 with GPS, 230VAC
HI 98291-01	HI 9829 and HI 7629829/4 pH, EC, DO, temperature, logging probe with 4 m (13.1') cable, 115VAC
HI 98291-02	HI 9829 and HI 7629829/4 pH, EC, DO, temperature, logging probe with 4 m (13.1') cable, 230VAC
HI 98292-01	HI 9829 and HI 7639829/4 pH, EC, DO, temperature, turbidity, logging probe with 4 m (13.1') cable, 115VAC
HI 98292-02	HI 9829 and HI 7639829/4 pH, EC, DO, temperature, turbidity, logging probe with 4 m (13.1') cable, 230VAC
HI 98293-01	HI 9829 and HI 7629829/10 pH, EC, DO, temperature, logging probe with 10 m (33') cable, 115VAC
HI 98293-02	HI 9829 and HI 7629829/10 pH, EC, DO, temperature, logging probe with 10 m (33') cable, 230VAC
HI 98294-01	HI 9829 and HI 7639829/10 pH, EC, DO, temperature, turbidity, logging probe with 10 m (33') cable, 115VAC
HI 98294-02	HI 9829 and HI 7639829/10 pH, EC, DO, temperature, turbidity, logging probe with 10 m (33') cable, 230VAC
HI 98295-01	HI 98290 with GPS and HI 7629829/4 pH, EC, DO, temperature, logging probe with 4 m (13.1') cable, 115VAC
HI 98295-02	HI 98290 with GPS and HI 7629829/4 pH, EC, DO, temperature, logging probe with 4 m (13.1') cable, 230VAC
HI 98296-01	HI 98290 with GPS and HI 7639829/4 pH, EC, DO, temperature, turbidity, logging probe with 4 m (13.1') cable, 115VAC
HI 98296-02	HI 98290 with GPS and HI 7639829/4 pH, EC, DO, temperature, turbidity, logging probe with 4 m (13.1') cable, 230VAC
HI 98297-01	HI 98290 with GPS and HI 7629829/10 pH, EC, DO, temperature, logging probe with 10 m (33') cable, 115VAC
HI 98297-02	HI 98290 with GPS and HI 7629829/10 pH, EC, DO, temperature, logging probe with 10 m (33') cable, 230VAC
HI 98298-01	HI 98290 with GPS and HI 7639829/10 pH, EC, DO, temperature, turbidity, logging probe with 10 m (33') cable, 115VAC
HI 98298-02	HI 98290 with GPS and HI 7639829/10 pH, EC, DO, temperature, turbidity, logging probe with 10 m (33') cable, 230VAC

PROBES

HI 7609829/4	pH, EC, DO, temperature probe with 4 m (13.1') cable
HI 7609829/10	pH, EC, DO, temperature probe with 10 m (33') cable
HI 7619829/4	pH, EC, DO, temperature, turbidity probe with 4 m (13.1') cable
HI 7619829/10	pH, EC, DO, temperature, turbidity probe with 10 m (33') cable
HI 7629829/4	pH, EC, DO, temperature, logging probe with 4 m (13.1') cable
HI 7629829/10	pH, EC, DO, temperature, logging probe with 10 m (33')cable
HI 7639829/4	pH, EC, DO, temperature, turbidity logging probe with 4 m (13.1') cable
HI 7639829/10	pH, EC, DO, temperature, turbidity logging probe with 10 m (33') cable

SENSOR MODULES

HI 7609829-0	pH
HI 7609829-1	pH/ORP
HI 7609829-2	Dissolved oxygen
HI 7609829-3	EC
HI 7609829-4	EC/Turbidity
HI 7609829-10	Ammonium ISE
HI 7609829-11	Chloride ISE
HI 7609829-12	Nitrate ISE

QUICK CALIBRATION SOLUTIONS

HI 9828-25	Quick calibration solution, 500 mL
HI 9828-27	Quick calibration solution, 1 G

pH CALIBRATION SOLUTIONS

HI 7004L	pH 4.01 buffer solution, 500 mL
HI 7007L	pH 7.01 buffer solution, 500 mL
HI 7010L	pH 10.01 buffer solution, 500 mL

ORP CALIBRATION SOLUTIONS

HI 7021L	ORP test solution @240 mV, 500 mL
HI 7022L	ORP test solution @470 mV, 500 mL

CONDUCTIVITY CALIBRATION SOLUTIONS

HI 7030L	12880 µS/cm calibration solution, 500 mL
HI 7031L	1413 µS/cm calibration solution, 500 mL
HI 7033L	84 µS/cm calibration solution, 500 mL
HI 7034L	80000 µS/cm calibration solution, 500 mL
HI 7035L	111800 µS/cm calibration solution, 500 mL
HI 7039L	5000 µS/cm calibration solution, 500 mL

TDS CALIBRATION SOLUTIONS

HI 7032L	1382 ppm (mg/L) calibration solution, 500 mL
HI 7036L	12.41 ppt (g/L) calibration solution, 500 mL

DISSOLVED OXYGEN SOLUTIONS

HI 7040L	Zero oxygen solution, 500 mL
HI 7042S	Electrolyte solution, 30 mL

CLEANING AND MAINTENANCE SOLUTIONS

HI 70300L	pH/ORP electrode storage solution, 500 mL
HI 7061L	pH/ORP electrode cleaning solution, 500 mL

ACCESSORIES

HI 929829	PC application software
HI 9698281	USB cable
HI 7698290	Short calibration beaker
HI 7698293	Long calibration beaker

P/L HI9829 1.0 03/11 PRINTED IN THE USA

PEWA GROUP
K&S Elektronik MB-electronic

PEWA
Messtechnik GmbH

Weidenweg 21
58239 Schwerte

Tel.: 02304-96109-0
Fax: 02304-96109-88
E-Mail: info@pewa.de
Homepage : www.pewa .de

HANNA® instruments
an ISO 9001:2000 CERTIFIED COMPANY