





Lamellenstecker

Ø 2mm – Ø 2,5mm



Multilam plugs

Ø 2mm – Ø 2,5mm

Typ Type Type	Bestell-Nr. Order No. No. de Cde	Nenn-Ø Nominal-Ø Ø nominal	Anschlussvariante Type of termination Type de raccordement	Metallteile / Oberfläche Metal parts / plating Partie métallique / traitement	Auszugskraft Withdrawal force Effort de débrochage	Obere Grenztemperatur Max. Temperature Température max.	Benennungsstrom ¹⁾ Rated current ¹⁾ Intensité assignée ¹⁾	Kontaktwiderstand Contact resistance Résistance de contact
		mm			N	°C	A	mΩ

SA200 22.1100 2 M2 CuZn, Au ~4 150 25 0,4

SA200N 22.1102 2 M2 CuZn, Ni ~4 150 25 2

Montagematerial bitte separat bestellen, siehe Seite 14.

Assembly material, please order separately, see page 14.

Accessoires de montage à commander séparément, voir page 14.

SA203 22.6303 2 Löten Soldering Souder CuZn, Ni ~4 150 25 2

SA2,5 22.5118 2,5 CuZn, Au ~6 150 25 0,5

SA2,5-G 22.5117 2,5 M2,5 CuZn, Au ~6 150 25 0,5

¹⁾ je nach Anschlussart und Querschnitt

¹⁾ According to connecting method and cross section

¹⁾ Selon la méthode de raccordement et la section du conducteur