

Advanced Contact Technology



Multi-Contact



STÄUBLI GROUP

□ 0,63 mm ... Ø 1,62 mm-
Messzubehör

□ 0.63 mm ... Ø 1.62 mm
Test Accessories

Accessoires de mesure
□ 0,63 mm ... Ø 1,62 mm

LK1,25-B



Hoch flexible Messleitung, beidseitig mit
Ø 1,25 mm-Buchse mit federnder Kontaktlamel-
le zur Aufnahme starrer Ø 1,25 mm-Stecker.

Highly flexible test lead with Ø 1.25 mm sockets
with spring-loaded Multilam on both ends ac-
cepting Ø 1.25 mm rigid plugs.

Cordon de mesure extra-souple, équipé des
deux côtés d'une douille à lamelles Ø 1,25 mm,
adaptée à la connexion de fiches rigides
Ø 1,25 mm.

Type Type Type	Best.-Nr. Order No. N° de Cde	Bemessungsspannung / -strom Rated voltage / current Tension / intensité assignée	Leitungsquerschnitt Lead cross section Section du câble		Längen [cm] Lead lengths [cm] Longueurs [cm]	*Farben *Colours *Couleurs
----------------------	-------------------------------------	--	---	--	--	----------------------------------

LK1,25-B

28.0023-□*

30 V_{AC} ~ 60 V_{DC} / 6 A

0,5 mm²

Au **PVC**

007 (7,5 cm)
015 **030** **045**

21 **22** **23** **24** **25**
26 **27** **28** **29**