Megger.

PowerDB[™]

Acceptance & Maintenance Test Data Management Software

		Parts tel																
112	1										×+	-	201	7.1				2
Press	t for f	form aperat	ion instruct	ionu	TR	ANSF	ORM		TUR	NS R	ATIC	TE	ST					
	M	legg	ger.				UT II						•••			Ę		
	CUST	OMER	XYZ E	ectrical Te	sting										- PA			
	-	HESS.	00264	36th Stree	r Omaha	NEADS	47							_		. 5	AND! E	02
				oczyk High							_	_		_	- ~		-mr LE	-vié
	VICER					1382 421	nd Stree	C ONA	na NE	08147			_			_		_
	OWN	ER REPRE	SENTATIVE	Tom	Sporne									TELEP	HONE _			
	DATE	10/1	8/2005	TEMPE	RATURE	4.4 +	HUME	NTY B	5 %	EGP	LOCAT	XON .		54	UN JAC	INTO		
		TATION			OUTDOO				-		STION .		_	NO	RTHS	DF		_
			-			-	_						_				_	_
	MAL			Tettary.						tpiler (at	ACT LOOP TO	# leaf set	a bhail annta	matcaly	back the	ratio cuto		-
ing #		2 Ohu		ph MFR	CP		VEA		1994	-	1.000	COLUMN STREET		ENC NAME		0.01000	10000	
	1.11		Sec. 1	SER S	COT		WEATHER OL TEM		UNIT .	- 269	USERA	LINUM	MFR			a iv	AMP'S	11EA
#C-9.4	Z	. 1	10 g	a weigh						· HI	1758-450	193	A00	0+		128	800	1990
73355	H.O-	* Dra		5. COOL			TANK TYP				1756-450		A40	0+		100	800	1000
		0 10	@ +##	TO PHAS		3	CLAS	6 <u>04</u>	CAFOA		2012/06/02		A-00	0.		120	1000	1000
	_		And a state of the local division of the loc	REAS	ON BO	vine in	NDG MAT		Ċ4		-	-		_		_	_	_
	12	1000	100.1100.0	20.20	02.000	diam'r.	ALLOWER			<u> </u>	1.1						1	
# Tests	PERM		TAGE (PTV)		IDI MTA	IS NOW	200	GER D	PSETTS	8	_	_	-	_	_	_	-	-
10	1000		1 80		344 - 51	- 17	-	-	_	_	-		_	_	_			
	00000	And the second second		-00 1 5			-	-										
		Votage Ro		west 10 yok		wat Row												
		dary Tap 15 vary Tap 15		000	25,900													
-raru	_		Anton		1000			ANSFOR										
	fest	PRIMARY	MC. TAP	HOH SEE VOL TAGE	LOW SCE VOLTAGE	RATIO	H 1 Date	11 3	/ X.1	-×1		# 1		XI		H 2 .	X 3	× 2
	<u> </u>	The second se	216 (1)	145.000	31.640	45770	1000	Then.	4940	holiant.	P961	Emr	16×C	Aufaha)	Ratio	Dutt	184	PTUTO
trument	1	Appropriate	214 221	145,000	21,000	#3448	-	-	-	-	-	-	-	-	-	-		-
OK.	1	Nominal	£14 (T)	145.000	29,443	49263	_	-	-			_	_	_	-			-
Auto	4	Nominal	#13 (4)	145,000	20,330	51182		10000				12 11			1000			1
	6	Nominal	#12 (1)	145,000	27,219	\$3209												
		Summa .	A(11 (6)	145,000	26,090	3.5577										1		
	1	RUNITA	#10 (7)	145,000	24,970	3.8010	-	-	-	_	-	-	-	_	-	_	_	-
		Reading of	85 (0)	145,000	23,840	6.3764						-			-			
	-	Automation of	477 1925	145.000	21,620	6.7068	-	-	-	_	_	_		_	-	_		_

- Windows-based PC software available in three versions
- Interfaces to instruments via either Serial RS232, Ethernet, or USB flash drive (depending on instrument)
- Allows user to set up test routines in advance of testing
- Allows analysis, comparison and trending of data
- User can customize the User Interface (test form view) with the ONBOARD and Full versions

DESCRIPTION

PowerDB is a powerful software package providing data management for each of your acceptance and maintenance testing jobs. Data can be imported from various sources, acquired directly from test instruments, or entered manually. Test results for all electrical apparatus are synchronized to your company's central database. Result and summary reports can be easily generated.

PowerDB Lite is free software allowing you to use standard PowerDB test forms with Megger instruments. It provides a simple and consistent user interface to many Megger instruments including the Delta 3000 power factor test set, 3-Phase TTR, earth testers and 5 and 10kV insulation testers.

PowerDB ONBOARD runs directly on the Megger test instrument, and the forms are the instrument's user interface. Test results are transferred with a standard USB drive and can then be read into PowerDB or PowerDB Lite.

Test Forms

Designed from a ground up approach, PowerDB utilizes over 200 industry standard test forms that have been developed and used over 20 years by industry specialists. Test data entry screens and printed forms are identical allowing intuitive operation. What you see on the screen is what is printed in the reports. Entire test documentation packages consisting of test reports, comment & deficiency summaries, table of contents and field service reports are created with a single step. Once created, reports can be delivered electronically via email, CD-ROM, web server or Adobe[®] Acrobat[®]. Test forms are designed for the majority of the electrical apparatus on the market today. PowerDB currently supports the following devices:

- Batteries
- Cables
- Circuit Breakers
- Coordination Data
- Disconnects
- Generators
- Ground Fault Tests
- Ground Mat/Grid Tests
- Instrument Transformers
- Power Transformers

The software will perform extensive information processing including equation calculations, temperature correction factors and charting. Data trending for predictive failure analysis is accomplished by charting historical results, stored in PowerDB or imported from other party's proprietary database software, for any piece of equipment.

PowerDB provides a powerful editor to create or customize forms. No database knowledge is required. Simply drag-and-drop tables, text boxes, images, charts, and more into a form. VBScript[®] can be used to define calculations, use lookup tables, and even interface with other applications. Sections common to multiple forms, such as logos, headers and footers, can be defined once and included in many forms. Also, one change updates all forms where it is used.

- Insulation Fluids
- Loadbreak Switches
- Motor Control Centers
- Power Factor Tests
- Relays
 - Switchboards
 - Transfer Switches
 - Watthour Meters
 - Transducers



PowerDB further provides test instrument control as well as data acquisition and supports many popular Megger products including:

- DELTA2000 and DELT3000, Power Factor Test Set
- TTR, Transformer Turns Ratio Test Set
- DLRO-200, Low Resistance Ohmmeter
- PULSAR and MPRT, Protective Relay Test Sets
- 5 and 10 kV Insulation Resistance Test Sets




Figure 1: Data Entry & Automated Control of Megger DELTA-2000

Test Documentation

Test documentation in PowerDB is accomplished in three ways:

- Manual data entry
- Importing data from other sources
- Data acquisition from test instruments

Manual data entry is done on screens identical in layout to the printed test forms. Importing data can be done from files designed for PowerDB by an equipment manufacturer or analysis laboratory. PowerDB test forms can also be designed to interact with other testing applications, such as Megger's Advanced Visual Test Software, AVTS. This interaction allows the population of test forms in PowerDB as tests are performed by the other application. Finally, data fields can also be populated by direct communication with popular Megger instruments as well as other brands of test equipment.

Trending

PowerDB allows on-the-fly trending of any test point. See Figure 2. Historical values for the particular equipment are shown in blue with connecting lines. All values for similar equipment are shown in red. A 2-sigma band is shown in green. A table above the trend chart lists all of the data values, as well as the test date and equipment location. Any record in this list may be selected to open the associated form with the detailed test results. This can be used to identify stray test values and review the test form to see what corrective actions were taken.




Figure 2: Trending (On-the-fly)

PowerDB can also import historical values for a piece of equipment from other third party proprietary database software allowing a seamless transition across software packages and/or test and measurement equipment.

Report Generation

Report generation in PowerDB for a group of tested equipment is done in one simple step. Customizable sorting allows adjustment of the test form order. Forms can be suppressed and page numbering adjusted. Supporting reports, such as the comment and deficiency summaries, can also be selected for printing at the same time. All test forms and supporting reports are sent to the printer in a single print job. Figure 3 shows the results ordering and print dialog.




Figure 3: Results Ordering and Printing

Comment and deficiency summary reports provide quick access to information collected across all equipment tested on a job. It also allows managers to review work without looking at hundreds of pages of test sheets. An example of a deficiency summary is shown in Figure 4.

In addition to generating reports directly through PowerDB, a web server is available which allows users to view reports on demand from anywhere. Only information pertinent to the particular web-access user is presented online.

Megger.

PB	Deficiency Summ Job #:2001-063		
			PAGE 1 of 1
Customer	Electrical Testing Company		
User	Woodlawn Hospital		
Plant	Woodlawn Hospital		
Substation:	м	Position:	M3 MCC-E201
Equipment:	15000 - LOW VOLT. PWR. CKT. BKR. TEST	Test Date and Ta	me: 3/12/2002 2:46:26 PM
Substation:	M	Position:	MAIN
Equipment:	15000 - LOW VOLT. PWR. CKT. BKR. TEST	Test Date and Tir	me: 8/7/2002 9:30:17 AM
	OULD NOT CHANNER PROPERLY INCIDENT OCCURED TWO R CLOSING ON CHANGING CYCLE	DE RACKING THE BREAKER OUT	AND BACK WOULD Page 135
Substation:	NA	Position: ELET	ATOR DIST. PNL
Equipment:	15600 + FUSE DISCONNECTED INSP. TEST	Test Date and Tir	ne: 5/14/2002 9:31:32 AM
··· CONTACT RESISTANCE OUT OF	TOLEPANCE PER NETA SPECIFICATIONS. SWITCH IS DEF	ECTIVE.	Page



COMPUTERIZED MAINTENANCE MANAGEMENT SYSTEM SUPPORT

Many electrical utilities and other company operations have invested in sophisticated CMMS systems, such as Digital Inspection's Cascade and MRO Software's MAXIMO. However, due to test instrument specific software packages and hand-written test results, these firms often struggle to get test data into their systems. One electric utility even referred to getting data into the CMMS as 'feeding the monster'. PowerDB's specialty IS 'feeding the monster'. PowerDB allows you to link easily with the CMMS system so that the system can pre-populate the PowerDB equipment database, send PowerDB all work orders, add forms based on the job plans, and even return the measurement points, obtained from a multitude of test sets, back to the CMMS system.

Furthermore, Megger will work directly with your CMMS personnel to integrate your data into your internal CMMS system.

FEATURES AND BENEFITS

- **200+ Industry Standard Test Forms Are Provided:** developed and used over 20 years by industry specialists
- **Data Trending for Predictive Failure Analysis:** chart historical results for any piece of equipment
- Built-in Information Processing: equation calculations, temperature correction factors, charting
- Create New Forms or Customize Our Forms: powerful forms editor is integrated, no database knowledge needed
- One-Step Generation of Entire Client Documentation Package: test forms, comment & deficiency summaries, table of contents, field service reports
- Deliver Reports Electronically: via email, via cd, via web server, via Adobe® Acrobat®

SELECTION GUIDE	PowerDB Version					
	LITE	FULL	ONBOARD			
Uses a subset of standard PowerDB forms applicable to your instrument						
Completed forms are saved as files to your computer						
Each file maintains historical results for an asset						
Files can read into the full version of PowerDB						
200+ industry standard test forms are provided						
Manages data for all electrical equipment						
Trending on any field allows predictive failure analysis						
Control instruments and download test data						
Import data from other software packages						
Contains all the features of PowerDB Lite						
Runs in a hardened embedded environment						
Navigate with arrow and enter keys (no mouse)						
Manage data files with internal drive and USB drive						

Megger.

 Test Data Entry Screens and Printed Forms Are Identical: what you see on the screen is what is printed

in the reports, streamlines data entry

- Job Tracking to Organize Contract Information: job test data, reports, quickly search and sort historical data
- Distributed Data Management: create subsets of data for field testing, merge results with another database
- Powerful Results Report Ordering: sort by standard fields, sort by any fields you define, easy manual page ordering
- Work Order Generation: trigger work orders through test schedule reports
- Import Data From Other Sources: Weidmann-ACTI, Doble, Oncor, TJH2b, Megger AVTS, Enoserv RTS, and more
- Test Instrument Control and Data Acquisition: Megger PULSAR, MPRT, DLRO 200, DELTA 2000, 3 Phase TTR, 5 and 10kV Megger Insulation Test Sets, Doble F2000, SMC Relay Test Set, Phenix, ETI-20, Fluke ScopeMeter, and more.

Optional Add-ons

PowerDB Web Server

The PowerDB Web Server allows you to deliver job documentation to your clients via your Microsoft Web Server. The entry screen for the PowerDB Web Server may also be used to deliver information promoting your company's services. The web server can also pass the web link to the actual test form to a CMMS system. This allows anyone viewing the work order in the CMMS system to click on the link and to transparently view their actual data sheet.

Any user can log into the PowerDB Web Server by providing a user name and password. They are then able to view each of their jobs, while other jobs are hidden from view. Job equipment information is presented in a tree hierarchy similar to how it is presented in PowerDB. Test reports of recent or historical data for any piece of equipment can be viewed individually. The PowerDB Web Server also allows you to deliver any other electronic documents that you submit for a job, such as a jobdocumentation package.

Microsoft SQL Server Upgrade

The SQL Server upgrade option functions identically to the Access version but supports larger databases and provides a substantial performance increase. PowerDB can seamlessly interact with Access field databases and SQL master databases.

On Site Training

A two day training course can be provided at your facility. Training includes data entry, trending, report generation, data synchronization and forms design.

CMMS Integration

For a flat fee, a PowerDB programmer will aid you in integrating a data exchange service between PowerDB and your CMMS system (or any other system). This service includes up to one week of on-site integration.

MINIMUM PC SYSTEM REQUIREMENTS

Processor

300 MHz Pentium Class processor minimum, 1 GHz or better recommended

Operating Systems Supported

Windows® Vista, 2000 and XP

System Memory (RAM)

64 MB RAM minimum, 512+ MB RAM recommended

Other Drives

Monitor/Display

800 x 600 resolution color monitor

Languages

English

PowerDB is a trademark of PowerDB, Inc., a subsidiary of Megger

ORDERING INFORMATION

ltem (Qty)	Cat. No.
PowerDB Software – 1st copy	DB1001
PowerDB Software – 1st copy w/usb	DB1001S
PowerDB Software – 2-5 ea copy	DB1002
PowerDB Software – 2-5 ea copy w/usb	DB1002S
PowerDB Software – 6+ ea copy	DB1003
PowerDB Software – 6+ ea copy w/usb	DB1003S
PowerDB Web Server Version	DB1004
PowerDB SQL Server Version	DB1005
PowerDB Software Support	DB2000
PowerDB Custom Forms – per page	DB2001
PowerDB CMMS Integration	DB2002
PowerDB Software Training	DB3000



PEWA Messtechnik GmbH

Weidenweg 21 58239 Schwerte

Tel.: 02304-96109-0 Fax: 02304-96109-88 E-Mail: info@pewa.de Homepage : www.pewa .de