



Linear transducer, TLH 225



Linear transducer, TS 25



Rotary transducer, Novotechnic IP6501 (analog)



Rotary transducer, Baumer BDH (digital)




Rotary transducer mounting kit



Switch magnetic base



Cable reels, 20 m (65.5 ft), 4 mm stack-able safety plugs



Universal support

Item	Description	TM1800	TM1600	EGIL	Art. No.
Ethernet cable, network	For connection to network	X			GA-00960
Vibration testing					
SCA606	Signal Conditioning Amplifier. Power supply, amplifier and signal conditioning filter for vibration testing using accelerometers with built-in charge amplifiers. (Note: DTW-analysis software needed)		X		BL-13096
Vibration analysis software	CABA option for DTW-analysis		X		BL-8270X
Accelerometer	DYTRAN 3200B5		X		XB-32010
Synchronized Switching Relay test kit					
SSR kit incl. accessories, software and cables (delivered in transport case)	SSR kit for TM1800	X			CG-91200
	SSR for TM1600 (incl. VD401)		X		BL-91200
Dynamic resistance measurement					
DRM1000	Dynamic resistance measurement of breaker contacts. Controls injection current up to 1000 A. External supply 12 V DC. Delivered complete, including the following:		X		BL-90041
	• Control unit DRM1000 incl. cable KG-00702 (red) and cable KG-00706 (blue) with snap-on connectors for a sealed 12 V battery.		X		BL-90040
	• Connection box		X		BL-90035
	• Sensing cables, 2 x 2 m, (6.5 ft) with clamps for connecting the circuit breaker to the connection box		X		GA-00430
	• Transport case		X		50-00110
DRM for TM1800	(To be released)	X			
Current cables	100 A		X		GA-00424
	250 A		X		GA-00422
	1000 A		X		GA-00420
Other					
VD401	Voltage divider, ratio 400/1 (for TM1600 and EGIL with analog channel)		X	X	BL-90070
PIR adapter	The adapter is used to test circuit breakers with pre-insertion resistors, when the resistance is lower than 250 \wedge or higher than 3000 \wedge . There are two versions:				
	PIR, 15 – 250 \wedge		X		BL-90080
	PIR2, 90 – 4500 \wedge		X		BL-90082
Current	AC/DC clamp/clip-on/current probe, Fluke 80i-110s				
	Current sensor kit 1 channel (Fluke 80i-110s incl. cable GA-00140)	X	X		BL-90600
	Current sensor kit 3 channels (Fluke 80i-110s incl. cables GA-00140)	X	X		BL-90610
Temperature sensor	For ambient temperature measurement (To be released)	X			
Long term monotoring	EPROM to be mounted in the TM1600				
LTM1	Starts measurement when there is a change at any of the time-measuring inputs		X		BL-80010
LTM2	Functions in the same way as a standard TM1600, but returns automatically to the READY state after measurement		X		BL-80011
Thermopaper	114 mm, 30 m		X	X	GC-00030
Thermopaper	114 mm, Ø 40 mm	X			GC-00040
Soft case		X			GD-00340

For more information about optional accessories please contact GE Energy.



Signal conditioning amplifier, SCA606



Cable reel, BL-90060



Extension cable XL, GA-00150



Accelerometer, Dytran 3200B5 and cable



DRM1000



Voltage divider, VD401



PIR adapter



Soft case