



Model 6442
13mm Tip Reach, SMD Micro
Grabber Test Clip 



FEATURES:

- ✓ Use with PQFP, SOIC, TSOP & SSOP packages with 0.3 lead pitch or greater.
- ✓ 13mm long tip allow's measurement at IC leads that are not easily accessible.
- ✓ Maximum frequency is 100 MHz.

MATERIALS:

Leads: Stainless-Steel Wire
Tip Tubing: Teflon™ Coated Nickel Plated Copper
Body: ABS
Flying Lead Connection: Gold Plated Copper

RATINGS:

Operating Voltage: Hands free usage in controlled voltage environments; 70 Vrms maximum. *For CE compliance:* not intended for hand-held use at voltages above 33 Vrms/70 Vdc.

ORDERING INFORMATION:

Model 6442 (Kit contains ten test clips and ten flying leads)



All dimensions are in inches. Tolerances (except noted): .XX = ±.02" (.51 mm), .XXX = ±.005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)
For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com

Pomona[®]

The items included with this product are certified to meet IEC 1010-2-031 safety requirements.

Les éléments inclus avec ce produit sont certifiés pour répondre à des exigences de sûreté du IEC 1010-2-031.

Los items incluidos con este producto se certifican para resolver requisitos de seguridad del IEC 1010-2-031.

– Only IEC 1010 type shrouded test plugs should be used with IEC 1010 type jacks. NEVER INSERT A PROBE TIP WITH BANANA SPRING INTO A TEST ACCESSORY JACK THAT WILL BE USED AS A HAND HELD PROBING DEVICE.

–Seuls les vérificateurs de tension renforcés de type IEC 1010 devraient être utilisés avec des jacks de type IEC 1010. NE JAMAIS INSERER DE BOUT DE SONDE AVEC BRESSORT BANANE DANS UN JACK D'ESSAI D'ACCESSOIRES QUI SERA UTILISE COMME DISPOSITIF DE SONDAGE A MAIN.

–Se deben usar sólo tapones de prueba reforzados del tipo IEC 1010 con receptáculos de tipo IEC 1010. NUNCA INTRODUCIR UNA CLAVIA CON UN MUELLE TIPO BANANA EN UN RECEPTACULO DE PRUEBA QUE A SU VEZ SE USE COMO APARATO DE PRUEBA MANUAL.



Both Direct and Alternating Current.
Courant Continu et Alternatif.



Double Insulation or Reinforced Insulation.
Isolation Double ou Isolation Renforcée.

CAT


Overvoltage Category I, II, III or IV.
Surtension Catégorie I, II, III ou IV.



Caution ! Refer to Accompanying Documents.
Attention ! Se Reporter aux Documents joints.



Caution ! Risk of Electric Shock.
Attention ! Risque de Choc Electrique.

Pomona Electronics 

PO Box 9090, Everett, WA 98206-9090 TEL: 800-490-2361