

Messtechnik GmbH Weidenweg 21 58239 Schwerte Tel.: 02304-96109-0

Tel.: 02304-96109-0 Fax: 02304-96109-88 E-Mail: info@pewa.de Homepage: www.pewa.de

## Model 72999 SMB PLUG PANEL RECEPTACLE



Model 72999 SMB PLUG PANEL RECEPTACLE

# Snap-on coupling and small size for fast connect and disconnect.

### **Features**

- DC 2 GHz bandwidth.
- Meets MIL-C-39012, IEC 60169-1Q, BS9210N0007, NFC93650, CECC 22130.
- Small size and durability for RF coaxial applications.
- Precision machined and gold-plated for low loss.

#### **Materials**

- Body is machined brass with gold plating.
- Center contacts Plug is gold plated brass and Jack is gold plated beryllium copper.
- High quality PTFE insulators.
- Crimp Ferrules are nickel plated copper.
- Silicone rubber gaskets.

## **Ordering Information**

Model: 72999

Description: SMB PLUG PANEL RECEPTACLE


USA: Sales: 800-490-2361

Technical Support: <a href="mailto:technicalsupport@pomonatest.com">technicalsupport@pomonatest.com</a>

Fax: 425-446-5844

**Europe:** 31-(0) 40 2675 150 **International**: 425-446-5500

Where to Buy: www.pomonaelectronics.com



## **Specifications**

50 Ω
DC – 2 GHz
1.3 max.
250 Vrms max.
750 Vrms
0.006/0.002 mΩ
500 cycles min.
1000 MΩ min.
-65° C to 165° C, -85° F to 329° F

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (.51 mm),  $.xxx = \pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

D2003436 REV 001