



2/3 Channel
High Performance
Power Supply

EasyArb function for free definable
V/I characteristics

FuseLink: individual channel
combination of electronic fuses


Free adjustable overvoltage protection
(OVP) for all outputs

Rear connectors for all channels
including sense

Versatility – One for All



www.hameg.com



4A-WY8H-MP0E · C&E_1108 · Subject to alterations · © HAMEG Instruments GmbH®
DQS-certified in accordance with DIN EN ISO 9001:2000, Reg.-No.: DE-071040 QM
HAMEG Instruments GmbH · Industriestr. 6 · D-63533 Mainhausen · Tel +49 (0) 6182 800 0
Fax +49 (0) 6182 800 100 · www.hameg.com · info@hameg.com · Made in Germany

Versatility – One for All



Power Supply

200W
400W



HMP
Series



HAMEG
Instruments
A Rohde & Schwarz Company

2/3 Channel High Performance Power Supply

HMP2020: 0...32V/0...10A 0...5.5V/0...5A

HMP2030: 2 x 0...32V/0...5A 0...5.5V/0...5A

HMP4030: 3 x 0...32V/0...10A

188W (HMP20x0), 384W (HMP4030) output power realized by intelligent power management

Low residual ripple: < 150 μ V_{rms} due to linear post regulators

High setting and read-back resolution of 1mV / 0.1mA

Galvanically isolated, earth free output channels

Advanced parallel and serial operation via V/I tracking

All parameters clearly displayed via LCD / glowing buttons

USB/RS-232 Interface, optional Ethernet/USB or IEEE-488



Accessories supplied: Line cord, Operating manual, Dual-Interface USB/RS-232 (H0720), CD

Optional accessories:

H0730 Dual-Interface Ethernet/USB

H0740 Interface IEEE-488 (GPIB), galvanically isolated

HZ10S 5 x silicone test lead (measurement connection in black)

HZ10R 5 x silicone test lead (measurement connection in red)


HZ42 2RU 19" Rackmount Kit (HMP2020, HMP2030)

HZ43 3RU 19" Rackmount Kit (HMP4030)



EasyArb functionality for simple voltage- and current characteristics

Rear outputs for simple integration in rack systems



Ethernet/USB-interface H0730 for industrial use (Option)

