

PEWA Messtechnik GmbH

Weidenweg 21 58239 Schwerte

Tel.: 02304-96109-0 Fax: 02304-96109-88 E-Mail: info@pewa.de Homepage : www.pewa .de



Product Features

- With dewpoint calculation °F td (testo 605-H1) or psychrometric wet bulb temperature calculation °F Tw (testo 605-H2)
- Humidity sensor unaffected by condensation
- Use clip for attachment to breast pocket
- Sensor protected by pivotable protection cap, long measurement stick 4.9 in.
- · With flexible joint
- · User-friendly
- Humidity sensor is not damaged by water saturation
- Auto OFF function
- A quick twist and the humidity sensor is protected by the attached cap
- · Swivel head, patented

605-H2 Humidity Stick

Product Overview

These low-cost test sticks are perfect for spot checking HVAC system performance. The 605-H2 Humidity Stick provides fast and accurate % RH, temperature, and wet bulb readings. Features one button operation, protective cap, pocket clip and water resistant sensor.

Humidity measurement stick, with duct holder, incl. multifunction clip and battery

Testo 605, the humidity measurement stick you can bend. Small, compact and accurate. The sensor remains stable in the long term guaranteeing accurate results even after years of use.

Product Specifications

- Probe type NTC
- Meas. range +32 to +122 °F
- Accuracy ±0.9 °F (+32 to +122 °F)
- Resolution 0.1 °F (+32 to +122 °F)
- Probe type humid. sensor, cap.
- Meas. Range +5 to +95 %RH
- Resolution 0.1 %RH
- Storage temperature -4 to +158 °F
- Operating temperature +32 to +122 °F
- Battery type 3V button cell (CR 2032)
- . Battery life 200 hr
- · Weight 4 oz